


STRIPLED FR3528-2835-5630 DC12V



Specifiche tecniche:

Modello: FR3528-60 FR3528-60	Tensione: 12Vdc 12Vdc	Potenza: 24W 24W	LED/metro 60 60	W/metro 4,8 4,8	CRI >72 >80	Lm/metro da 360 a 420 da 420 a 480	CCT (°K) 3000 - 4000 3000 - 4000	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)	Grado di protezione: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)
Modello: FR3528-120 FR3528-120	Tensione: 12Vdc 12Vdc	Potenza: 48W 48W	LED/metro 120 120	W/metro 9,6 9,6	CRI >72 >80	Lm/metro da 720 a 840 da 840 a 960	CCT (°K) 3000 - 4000 3000 - 4000	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)
Modello: FR2835-60 FR2835-60	Tensione: 12Vdc 12Vdc	Potenza: 60W 60W	LED/metro 60 60	W/metro 12 12	CRI >72 >80	Lm/metro da 1380 a 1500 da 1440 a 1560	CCT (°K) 3000 - 4000 3000 - 4000	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)
Modello: FR2835-120 FR2835-120	Tensione: 12Vdc 12Vdc	Potenza: 90W 90W	LED/metro 120 120	W/metro 18 18	CRI >72 >80	Lm/metro da 2760 a 3000 da 2880 a 3120	CCT (°K) 3000 - 4000 - 5000 3000 - 4000 - 5000	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)	Dimensioni: 5000x8x1,5mm (IP20) 5000x8x1,5mm (IP20)
Modello: FR5630-30 FR5630-30	Tensione: 12Vdc 12Vdc	Potenza: 45W 45W	LED/metro 30 30	W/metro 9 9	CRI >72 >80	Lm/metro da 1350 a 1650 da 1650 a 1800	CCT (°K) 3000 - 4000 3000 - 4000	Dimensioni: 5000x10x1,5mm (IP20) 5000x10x1,5mm (IP20)	Dimensioni: 5000x10x1,5mm (IP20) 5000x10x1,5mm (IP20)
Modello: FR5630-60 FR5630-60	Tensione: 12Vdc 12Vdc	Potenza: 90W 90W	LED/metro 60 60	W/metro 18 18	CRI >72 >80	Lm/metro da 2700 a 3300 da 3300 a 3600	CCT (°K) 3000 - 4000 - 5000 3000 - 4000 - 5000	Dimensioni: 5000x10x1,5mm (IP20) 5000x10x1,5mm (IP20)	Dimensioni: 5000x10x1,5mm (IP20) 5000x10x1,5mm (IP20)

FR3528 (dimensioni IP65-IP68)



Note: disponibili solo su ordinazione altre temperature di colore da 2200 a 6500°K, e la versione IP68.

FR5630 (dimensioni IP65)

