


STRIPLED FR3528-2835-5630 DC24V



Specifiche tecniche:

Modello: FR3528-60	Tensione: 24Vdc	Potenza: 24W	LED/metro 60	W/metro 4,8	CRI >72	Lm/metro da 360 a 420	CCT (°K) 3000 - 4000	Dimensioni: 5000x8x1,5mm (IP20)	Grado di protezione: 5000x8x1,5mm (IP20)
FR3528-60	24Vdc	24W	60	4,8	>80	da 420 a 480	3000 - 4000	5000x8x1,5mm (IP20)	5000x8x1,5mm (IP20)
Modello: FR3528-120	Tensione: 24Vdc	Potenza: 48W	LED/metro 120	W/metro 9,6	CRI >72	Lm/metro da 720 a 840	CCT (°K) 3000 - 4000	Dimensioni: 5000x8x1,5mm (IP20)	Dimensioni: 5000x8x1,5mm (IP20)
FR3528-120	24Vdc	48W	120	9,6	>80	da 840 a 960	3000 - 4000	5000x8x1,5mm (IP20)	5000x8x1,5mm (IP20)
Modello: FR2835-60	Tensione: 24Vdc	Potenza: 60W	LED/metro 60	W/metro 12	CRI >72	Lm/metro da 1380 a 1500	CCT (°K) 3000 - 4000	Dimensioni: 5000x8x1,5mm (IP20)	Dimensioni: 5000x8x1,5mm (IP20)
FR2835-60	24Vdc	60W	60	12	>80	da 1440 a 1560	3000 - 4000	5000x8x1,5mm (IP20)	5000x8x1,5mm (IP20)
Modello: FR2835-120	Tensione: 24Vdc	Potenza: 90W	LED/metro 120	W/metro 18	CRI >72	Lm/metro da 2760 a 3000	CCT (°K) 3000 - 4000 - 5000	Dimensioni: 5000x8x1,5mm (IP20)	Dimensioni: 5000x8x1,5mm (IP20)
FR2835-120	24Vdc	90W	120	18	>80	da 2880 a 3120	3000 - 4000 - 5000	5000x8x1,5mm (IP20)	5000x8x1,5mm (IP20)
Modello: FR5630-30	Tensione: 24Vdc	Potenza: 45W	LED/metro 30	W/metro 9	CRI >72	Lm/metro da 1350 a 1650	CCT (°K) 3000 - 4000	Dimensioni: 5000x10x1,5mm (IP20)	Dimensioni: 5000x10x1,5mm (IP20)
FR5630-30	24Vdc	45W	30	9	>80	da 1650 a 1800	3000 - 4000	5000x10x1,5mm (IP20)	5000x10x1,5mm (IP20)
Modello: FR5630-60	Tensione: 24Vdc	Potenza: 90W	LED/metro 60	W/metro 18	CRI >72	Lm/metro da 2700 a 3300	CCT (°K) 3000 - 4000	Dimensioni: 5000x10x1,5mm (IP20)	Dimensioni: 5000x10x1,5mm (IP20)
FR5630-60	24Vdc	90W	60	18	>80	da 3300 a 3600	3000 - 4000	5000x10x1,5mm (IP20)	5000x10x1,5mm (IP20)

FR3528 (dimensioni IP65)



Note: disponibili solo su ordinazione altre temperature di colore da 2200 a 6500°K, e la versione IP68.

FR5630 (dimensioni IP65)

