

STRIPLED



Specifiche tecniche:


Modello:

STRTWI600W24
 STRTWI600N24
 STRTWI600C24
 STRTWI600W24NP
 STRTWI600N24NP
 STRTWI600C24NP
 STRTWI300WA
 STRTWI300NA
 STRTWI300WAP
 STRTWI300NAP
 STRTWI300N24
 STRTWI300W24
 STRTWI150N
 STRTWI150W
 STRTWI300N
 STRTWI300WP
 STRTWI300NPN
 STRTWI300WNP
 STRAVT300N(684)
 STRAVT600N1(680)
 STRAVT600N(663)

Descrizione:

2835 18W 24V 3000°K IP65 CRI>80 120 led/m 24-26lm/led 2880-3120 lm/m
 2835 18W 24V 4000°K IP65 CRI>80 120 led/m 24-26lm/led 2880-3120 lm/m
 2835 18W 24V 5000°K IP65 CRI>80 120 led/m 24-26lm/led 2880-3120 lm/m
 2835 18W 24V 3000°K IP20 CRI>80 120 led/m 24-26lm/led 2880-3120 lm/m
 2835 18W 24V 4000°K IP20 CRI>80 120 led/m 24-26lm/led 2880-3120 lm/m
 2835 18W 24V 5000°K IP20 CRI>80 120 led/m 24-26lm/led 2880-3120 lm/m
 2835 12W 12V 3000°K IP20 CRI>72 60 led/m 23-25lm/led 1380-1500lm/m
 2835 12W 12V 4000°K IP20 CRI>72 60 led/m 23-25lm/led 1380-1500lm/m
 2835 12W 12V 3000°K IP65 CRI>72 60 led/m 23-25lm/led 1380-1500lm/m
 2835 12W 12V 4000°K IP65 CRI>72 60 led/m 23-25lm/led 1380-1500lm/m
 5630 18W 24V 4000°K IP20 CRI>80 60 led/m 55-60lm/led 3300-3600lm/m
 5630 18W 24V 3000°K IP20 CRI>80 60 led/m 55-60lm/led 3300-3600lm/m
 5630 9W 12V 4000°K IP20 CRI>80 30led/m 55-60lm/led 1650-1800lm/m
 5630 9W 12V 3000°K IP20 CRI>80 30led/m 55-60lm/led 1650-1800lm/m
 3528 4,8W 12V 4000°K IP65 CRI>80 60 led/m 7-8lm/led 420-480lm/m
 3528 4,8W 12V 3000°K IP65 CRI>80 60 led/m 7-8lm/led 420-480lm/m
 3528 4,8W 12V 4000°K IP20 CRI>80 60 led/m 7-8lm/led 420-480lm/m
 3528 4,8W 12V 3000°K IP20 CRI>80 60 led/m 7-8lm/led 420-480lm/m
 4,8W 12V 4000°K IP65 CRI>72
 9,6W 12V 4000°K IP65 CRI>72
 9,6W 12V 4000°K IP20 CRI>72

FR3528 (dimensioni IP65)



Note: disponibili solo su ordinazione altre temperature di colore da 2200 a 6500°K, e la versione IP68.

FR5630 (dimensioni IP65)

